



• One channel control unit

Use:
Electro-permanent magnetics modules for milling / grinding

- Features:**
- Multiple input voltage choices
 - Micro computer controls self testing and magnetizing detection
 - Good for both 50 Hz and 60 Hz
 - PLC connection built in
 - Safe and reliable
 - Including 5 meters power cable and 5 meters discharge cable



• Two channels control unit

Use:
Electro-permanent magnetics modules for milling / grinding

- Features:**
- Multiple input voltage choices
 - Micro computer controls self testing and magnetizing detection
 - Good for both 50 Hz and 60 Hz
 - PLC connection built in
 - Safe and reliable
 - Including 5 meters power cable and 5 meters discharge cable



Model	Length	Width	Height	Net weight	Box
CUT-A	325 (12.80)	170 (6.69)	90 (3.54)	3.4 kg / 7.5 lb	Metal

Model	Length	Width	Height	Net weight	Box
CUA-H	300 (11.81)	200 (7.87)	105 (4.13)	1.6 kg / 3.5 lb	Plastic
CGA-H	300 (11.81)	200 (7.87)	105 (4.13)	1.6 kg / 3.5 lb	Plastic

Voltage	Max. Pole No. / channel	Pole size
220 V	56	50 x 50 mm
400 / 480 V	84	50 x 50 mm

Model	Length	Width	Height	Net weight	Box
CUD-H	300 (11.81)	200 (7.87)	105 (4.13)	2.0 kg / 4.4 lb	Plastic
CGD-H	300 (11.81)	200 (7.87)	105 (4.13)	2.0 kg / 4.4 lb	Plastic

Voltage	Max. Pole No. / channel	Pole size
220 V	56	50 x 50 mm
400 / 480 V	84	50 x 50 mm

• Two channels control unit

Use:
Electro-permanent magnetics modules for milling

- Features:**
- Multiple input voltage choices
 - Micro computer controls self testing and magnetizing detection
 - Good for both 50 Hz and 60 Hz
 - PLC connection built in
 - Safe and reliable
 - Including 5 meters power cable and 5 meters discharge cable
 - With channel selection function

Voltage	Max. Pole No. / channel	Pole size
220 V	56	50 x 50 mm
400 / 480 V	84	50 x 50 mm